



Electrical Helper.org
 For All Your Electric Needs Since 1928
 411 N Platte Ave. York, NE. 68467

AC-DC MOTORS :: SALES & SERVICE
 REWINDING :: CUSTOM CONTROL PANEL

Kelly MacMillan
 Office Ph: 888-226-4917
 Fax: 888-226-4917
 Cell: 402-679-1579
 E-Mail: kelly@electricalhelper.com



DATA SHEET

Premium Efficiency Motor: **FD5-18-184T**,

60 Hz

Document Generated: 25-Sep-2024
 Document ID:

Customer:

MOTOR INFORMATION

HP	5
RPM	1800
Phase	1
Frequency	60 Hz
Voltage	230
Frame Size	184T
Enclosure	TEFC
Degree of Protection	IP55
Service Factor	1.15
Poles	4
Full Load Speed	1769
Insulation Class	F
Temp Rise	80°C
NEMA Code Letter	J
Duty Cycle	S1 / Continuous
Slip	1.72%
Max Ambient Temperature	40°C
Max Elevation	1000 m.a.s.l (3300 f.a.s.l)
Mounting	F1
Rotation	Bi-Directional
Mounting Type	Rigid Base
Standard	NEMA MG-1
Approvals	UL, CE

EFFICIENCY/POWER FACTOR

LOAD	EFF	P. F.
100%	86.4 %	92.2
75%	85.4 %	90.50
50%	81.0 %	85.9

TORQUE

FULL LOAD	LRT	BDT
14.74 lb.ft.	470 %	221 %

AMPERAGE INFORMATION

	230V
Full Load Amps	20.18A
Locked Rotor Amps	170.7A
No Load Current	6.32A
Usable at 208V	22.31A

BEARING INFORMATION

DE Bearing	6306ZZ C3
ODE Bearing	6206ZZ C3
Grease Type	NSK SN7

CAPACITOR INFORMATION

Start Capacitor	(1)550uF/330V
Run Capacitor	(1)50uF/450V

ADDITIONAL DATA

F2 Suitable	No
Shaft Material	1045 Carbon Steel
Connection Diagram	230V - 4 Lead
Approximate Weight	100.1 lbs.



Electrical Helper.org
 For All Your Electric Needs Since 1928
 411 N Platte Ave. York, NE. 68467

AC-DC MOTORS :: SALES & SERVICE
 REWINDING :: CUSTOM CONTROL PANEL
 Kelly MacMillan
 Office Ph: 888-226-4917
 Fax: 888-226-4917
 Cell: 402-679-1579
 E-Mail: kelly@electricalhelper.com



NAMEPLATE / WIRING

Premium Efficiency Motor: **FD5-18-184T**

Document Generated: 25-Sep-2024
 Document ID:

Customer:

SAMPLE NAMEPLATE DATA

		HIGH EFFICIENCY-HIGH TORQUE SINGLE PHASE FARM DUTY MOTOR			
Model :		SN :		Poles : 4	<p><u>RATED VOLTAGE</u></p> <p>CONNECTED FOR CCW ROTATION FACING OPPOSITE DRIVE END</p> <p>TO REVERSE ROTATION INTERCHANGE LEAD 5 & 8</p> <p>MOTOR MUST BE GROUNDED. USE GREEN LEAD IF SUPPLIED PER THE NATIONAL ELECTRICAL CODE</p>
HP :		Encl : TEFC		IP 55	
Hz :	60	FR :		Eff :	
Volts :	230	Ins : F		P.F. :	
Amps :		CODE :		DE BRG :	
RPM :		WT : LBS		ODE BRG :	
SF :	1.15	Max Amb 40°C - CONT		Date :	
WorldWide Electric Corporation					

Model	FD5-18-184T				
HP	5	Encl	TEFC	IP	IP55
Hz	60 Hz	Frame	184T	Nom.Eff.	86.4%
Voltage	230	Ins Cl	F	P.F.	92.2
Amps	20.18A	Code	J	DE Brng	6306ZZ C3
RPM	1769	WT:	100.1 lbs.	ODE Brng	6206ZZ C3
S.F.	1.15				